



Fünfhals-Rundkolben mit Normschliff-Hülse, 4 seittl. Hälse senkrecht	Ballons à fond rond avec 5 cols avec rodages normalisés femelles 4 cols latéraux droits	Flask round bottom and 4 side necks, parallel	2.139
---	--	--	--------------

Vol. ml	mittl. Hals col central Centre neck NS/RN	seittl. Hals col lateral Side neck NS/RN	
500	29/32	29/32	2.139.010
1000	29/32	29/32	2.139.020
1000	45/40	29/32	2.139.030
2000	29/32	29/32	2.139.040
2000	45/40	29/32	2.139.050
3000	29/32	29/32	2.139.060
3000	45/40	29/32	2.139.070
4000	29/32	29/32	2.139.080
4000	45/40	29/32	2.139.090
6000	29/32	29/32	2.139.100
6000	45/40	29/32	2.139.110
10000	45/40	29/32	2.139.120
20000	45/40	29/32	2.139.130



Stickstoff-Rundkolben (Schlenkkolben) mit NSH, seitlicher Hahn mit massivem Glasküken und Olive	Ballons à fond rond à azote (Ballons selon Schlenk) , col avec rodage normalisé femelle, robinet lat., clé massive et olive	Collecting flask acc. to Schlenk	2.140
--	--	---	--------------

Vol. ml	NS/RN	NS-Hahn RN robinet Stopcock	Bohrung mm passage mm Bore mm	
250	29/32	14	4	2.140.060
500	29/32	14	4	2.140.070
1000	29/32	14	4	2.140.080
2000	29/32	19	6	2.140.090
3000	29/32	19	6	2.140.100



Stickstoff-Rundkolben mit NS-Hülse, Ventilhahn mit PTFE-Spindel und Olive	Ballons à fond rond à azote avec rodage normalisé femelle avec robinet à pointeau en PTFE et olive	Nitrogen round bottom flask with PTFE valve	2.141
--	---	--	--------------

Vol. ml	NS/RN	Ventil mm pointeau mm Passage mm	
500	29/32	6	2.141.070
1000	29/32	6	2.141.080
2000	29/32	10	2.141.090
3000	29/32	10	2.141.100

