

Verbindungsstücke mit Normschliff und Olive		Raccord avec rodage normalisé et olive	Suction tube with ST-joints and hose connection	2.122
---	--	--	---	-------

NS-Kern
RN mâle
Cone NS

Olive mm
olive mm
hose mm

Ausführung gerade
exécution droite
straight


Ausführung gebogen
exécution coudée
bent

14/23
19/26
24/29
29/32
45/40

8
8
10
10
10

2.122.010
2.122.020
2.122.030
2.122.040
2.122.050

2.122.110
2.122.120
2.122.130
2.122.140
2.122.150




NS-Hülse
RN femelle
Socket NS

14/23
19/26
24/29
29/32
45/40

8
8
10
10
10

2.122.210
2.122.220
2.122.230
2.122.240
2.122.250

2.122.310
2.122.320
2.122.330
2.122.340
2.122.350



Ausführung mit Filterplatte wie folgt bestellen: z. B. 2.122.210P2 = mit Filterplatte POR 2

Exécution avec plaque filtrante commander comme suit: p. ex. 2.122.210P2 = avec plaque filtrante POR 2

Version with filter disc ordered as follows: f. e. 2.122.210P2 = with filter disc POR 2

Verbindungsstück mit Normschliff Hahn und Olive Hähne mit austauschbarem Glasreiber			Raccord avec rodage normalisé robinet et olive robinet à clé interchangeable	Suction tube with ST-stopcock and hose connection	2.123
---	--	--	--	---	-------

NS-Kern
RN mâle
Cone NS

NS-Hahn
RN robinet
Stopcock NS

Bohrung
passage
Bore

Olive mm
Olive mm
hose mm

Ausführung gerade
exécution droite
straight

Ausführung gebogen
exécution coudée
bent

14/23
19/26
24/29
29/32
45/40


14
14
14
14
19

2.5
2.5
4.0
4.0
6.0

8
8
10
10
10

2.123.010
2.123.020
2.123.030
2.123.040
2.123.050

2.123.110
2.123.120
2.123.130
2.123.140
2.123.150



NS-Hülse
RN-femelle
Socket NS

14/23
19/26
24/29
29/32
45/40


14
14
14
14
19

2.5
2.5
4.0
4.0
6.0

8
8
10
10
10

2.123.210
2.123.220
2.123.230
2.123.240
2.123.250

2.123.310
2.123.320
2.123.330
2.123.340
2.123.350



Ausführung mit Filterplatte wie folgt bestellen: z. B. 2.123.330P4 = mit Filterplatte POR 4

Exécution avec plaque filtrante commander comme suit: p. ex. 2.123.330P4 = avec plaque filtrante POR 4

Version with filter disc ordered as follows: f. e. 2.123.330P4 = with filter disc POR 4